






PRODUCT SPECIFICATIONS

- Certified Fire Retardant Door
- Made in fiberglass
- Watertight to 25 KN/m2
- Quick acting single handle locking system
- Hand-wheel operated locking system

Max clear opening 1800x650 (HxW)












- Door Locks (WT)
- FRD60 Windows (WT)
- Coating
- Door closer/Wind hook
- Open/Close proximity switch




Fiberglass FRD60 Door:

- No maintenance
- Lighter than other doors
- Quick acting adjustable dogs and hinges



Watertight to 25 KN/m2







STANDARD TYPE

- All moving parts stainless steel AISI 316
- Adjustable moving parts
- 100 mm corner radius
- Greaseless bearings
- Standard angle AISI 316 bar frame
- Excellent performance during fire
- Low maintenance, long lifetime
- Gel coat surface treatment
- Glass fiber reinforced plastic (GRP fire resistance door leaf)

BC Service's **FRD60 doors** are approved by **Lloyd's Register** according to the latest rules for classifications of ships, mobile offshore and HSC.

U-DOOR

The peculiarity of the BCS U-Door is that it is made of fiberglass, a material that is requested in certain applications, mainly high end yachting or military.


SAFETY AT SEA LEVEL

The U-Doors are designed for the most extreme conditions and are showing an excellent performance during fire testing and operational testing.

Very few fiberglass doors in the world are FRD60 FRD60 Water and Fire U-Doors are fully certified as fire

doors according to 2010 FTP Code.

Temperature inside the furnace 945° C after 60 min.





Temperature outside the furnace 50 °C after 60 min.



service@bcserviceinc.com sales@bcserviceinc.com bcservicegroup.com

United States 13181 NW 43rd Avenue Miami, FL 33054 United States **Italy** Via al Molo Giano 16128 Genova (GE) Italy

Singapore 16 Stanley Street Level 3 Singapore 068735 **China** Room 4-110, 2nd floor 2351 of West of Changjiang Road Baoshan District, Shanghai

service group.com